



AMAZON BUBBLER

BUBBLER/PRESSURE SENSOR

Designed with simplicity in mind, the Amazon bubbler is the ideal system for long-term, water level monitoring sites. It can be used as a stand-alone system with internal data storage, or as a sensor connected to any manufacturer's data logger. Easily configure and collect data using the browser-based graphical user interface with all standard web browsers on PCs, tablets and smart phones. It's rugged build, and technologically advanced system makes the Amazon Bubbler an attractive solution for real-time monitoring and data collection.

The Amazon provides a continuous air bubble and an integrated pressure sensor that measures the pressure required to push the bubble out of the orifice line, which is the line pressure. The line pressure value measured in psi is then converted into the desired units of measurement to represent water level.

APPLICATIONS

Accurately measure stream, lakes, wells, ocean and waste water levels.

KEY FEATURES

- Advanced rugged design
- Internal data logging
- Intuitive menu configuration
- High accuracy 0.02% FS
- Multiple output and connection options (SDI-12, Modbus, 4-20 mA, USB, Ethernet)
- Optional low-powered display for complete system configuration and data display.
- "Powered by Storm" technology:
 - W-Fi Connection Interface
 - Storm Central Connectivity
 - Browser based software
- Range options:
 - 0 to 10.5 m (34.6 ft)
 - 0 to 21 m (69.2 ft.)
 - 0 to 35 m (115 ft.)



Amazon Bubbler

*shown with optional display



a xylem brand

SPECIFICATIONS

PERFORMANCE			
Accuracy	Pressure	Less than or equal to 0.02% of full scale output (FSO) over temperature range	
	Range	Pressure	Depth Accuracy
Range	0 to 15 PSI	0 to 10.54 m (34.6 ft)	±2.1 mm (0.007 ft)
	0 to 30 PSI	0 to 21 m (69.20 ft)	±4.3 mm (0.014 ft)
	0 to 50 PSI	0 to 35.15 m (115.34 ft)	±7.11mm (0.02333 ft)
Bubbler Gas Delivery	Microprocessor controlled unit		
	Gas Flow Technology	Constant mass Technology	
	Gas Flow Control	Bubble rate is user programmable from 30 to 120 bubbles per minute based on 6.35 mm (1/4 in.) tubing.	
Purge Functions	Purge Pressure Level	User Selectable 40 PSI to 90 PSI	
	Options	<ul style="list-style-type: none"> • Manual • SDI driven purge • Purge sustain option (10 to 30 sec) • Automatic/programmable 	
Compressor	Type	Piston Compressor	
	Operation	Low duty cycle (15 hours typical runtime per year at 60 bubbles per minute into 3.7 m (12 ft.) (purges not included)	
General	Pressure Overload	Up to 2 times the rated pressure	
	Media Capability	Non-corrosive dry gases only	
	Rating	NEMA 4 enclosure	
MECHANICAL / POWER			
Size	Housing	311.15 mm L x 222.25 mm W x 146.05 mm H (12.25 in. L x 8.75 in. W x 5.75 in. H)	
Weight	Housing	5.44kg (12.0 lbs)	
Material	Housing	Aluminum	
	Atmospheric Vent	Sintered bronze, #10-32	
Power Requirements	Voltage Input	10.0 to 16.5 V DC	
	Current	Standby: 6mA	
		Compressor Active, No Pressure: 3 A	
		Compressor Active, Full Pressure: 6 A	
		Startup Surge Required: 15 A	
Based on a 60 bubbles/min flow rate with a 15 min measurement cycle and a 1 purge/day frequency. Average active current 20mA			

	Surge Protection	20 V DC
Connection	Quick Connect Phoenix Connectors	2-position quick connect for power
	Pressure Inlet	5-position quick connect for SDI-12, 4 to 20mA, and RS-485
		3.82 cm (1/8 in) female NPT
COMMUNICATION		
SDI-12	Baud Rate	1200
	Protocol	SDI-12 V1.3, 7-bit even parity, 1 stop bit
	Output Voltage Levels	Minimum high level: 3.5 volts Maximum low Low: 0.8 volts
	Response Time	8-second measurement sequence (programmable)
RS-485	Baud Rate	Programmable (default = 9600)
	Protocol	Modbus RTU
4-20mA Output	Type	4-20mA, optically isolated
	Loop Voltage	8.0V min, 35V max
	Resolution	±0.24 uA (16-bit DAC)
	Accuracy	0.075% max error
ENVIRONMENTAL		
General	Operating Temperature	-40° to +60° C
	Compensated Range	-40° to +60° C
	Storage Temperature	-60° to + 80° C
MISCELLANEOUS		
Warranty	The Amazon Bubbler is warranted against defects in materials and workmanship for two years from date of shipment.	
Note	Specifications subject to change without prior notice due to on going commitment to product testing and improvement. LR May 2016 (D59-06 0516)	

